

iMATIC 455

Automatic transmission fluid



Corresponds with requirements / specifications / products:

VW G 055 005 A1/A2/A6
ZF S671 090 252/253/255
BMW 832 20 142 516 (1375.4)/832 20 144 137
JAGUAR C2C 8432
MERCON SP
LAND ROVER TYK500050
HYUNDAI 040000C90SG

Volume:

1 L (PM0455-1) 10 L (PM0455-10)
20 L (PM0455-20) 60 L (PM0455-60)
208 L (PM0455-DR) 1000 L (PM0455-IBC)

Pemco iMATIC 455 is a multifunctional ATF for use in modern 6-speed automatic transmissions in cars and commercial vehicles. Meets the requirements of the most common specifications of European car manufacturers. Provides an excellent low-temperature switching behaviour, a stable high friction level and best wear protective properties for a reliable operation and a long life.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	840
Viscosity at 40 °C	D 445	cSt	28,60
Viscosity at 100 °C	D 445	cSt	6,05
Viscosity index	D 2270		166
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-52

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.